



## Safety Data Sheet

© 2021, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 29-8286-6 **Version number:** 4.00  
**Issue Date:** 04/03/2021 **Supersedes date:** 09/11/2020

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchbond™ Universal Etchant (41263)

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Etching gel

##### Restrictions on use

For use by dental professionals only.

#### 1.3. Supplier's details

**Address:** 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland  
**Telephone:** (09) 477 4040  
**E Mail:** innovation@nz.mmm.com  
**Website:** 3m.co.nz

#### 1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

### SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

GHS	HSNO
Corrosive to metal: Category 1	8.1A Corrosive to metals
Serious Eye Damage/Irritation: Category 1	8.3A Corrosive to eye
Skin Corrosion/Irritation: Category 1C	8.2C Corrosive to skin
No GHS Equivalent	9.3C Terrestrial vertebrate toxicity

#### 2.2. Label elements

**SIGNAL WORD**

DANGER!

**Symbols:**

Corrosion |

**Pictograms**



**HAZARD STATEMENTS:**

- |      |  |
|------|--|
| H290 | May be corrosive to metals.              |
| H314 | Causes severe skin burns and eye damage. |
| H433 | Harmful to terrestrial vertebrates.      |

**PRECAUTIONARY STATEMENTS**

**Prevention:**

- |       |   |
|-------|---|
| P234A | Keep only in original packaging.                                      |
| P260  | Do not breathe dust/fume/gas/mist/vapours/spray.                      |
| P280A | Wear eye/face protection.   |
| P280D | Wear protective gloves, protective clothing, and eye/face protection. |
| P273  | Avoid release to the environment.                                     |
| P264B | Wash exposed skin thoroughly after handling.                          |

**Response:**

- |                     |  |
|---------------------|--|
| P304 + P340         | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305 + P351 + P338  | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310                | Immediately call a POISON CENTER or doctor/physician.  |
| P363                | Wash contaminated clothing before reuse.   |
| P301 + P330 + P331  | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.   |
| P321                | Specific treatment (see Notes to Physician on this label).   |
| P390                | Absorb spillage to prevent material damage.  |
| P303 + P361 + P353A | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.                           |

**Storage:**

- |       |  |
|-------|--|
| P405  | Store locked up.   |
| P406A | Store in a corrosion resistant container with a resistant inner liner. |

**Disposal:**

- |      |  |
|------|--|
| P501 | Dispose of contents/container in accordance with applicable local/regional/national/international regulations. |
|------|--|

**2.3. Other hazards**

- May cause chemical gastrointestinal burns.

**SECTION 3: Composition/information on ingredients**

## 3M™ Scotchbond™ Universal Etchant (41263)

Ingredient	CAS Nbr	% by Weight
Water	7732-18-5	50 - 65
Phosphoric Acid	7664-38-2	30 - 40
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	5 - 10
Polyethylene Glycol	25322-68-3	1 - 5
Aluminium Oxide	1344-28-1	< 2

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

#### If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide.  
Carbon dioxide.

#### Condition

During combustion.  
During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### 5.4. Hazchem code: 2R

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

Refer to Section 15 - Controls for more information

**7.1. Precautions for safe handling**

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from strong bases.

**7.3. Certified handler**

Not required

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Aluminium Oxide	1344-28-1	New Zealand WES	TWA(8 hours):10 mg/m <sup>3</sup>	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m <sup>3</sup>	A4: Not class. as human carcinogen
Polyethylene Glycol	25322-68-3	AIHA	TWA(as aerosol):10 mg/m <sup>3</sup>	
Phosphoric Acid	7664-38-2	ACGIH	TWA: 1 mg/m <sup>3</sup> ; STEL: 3 mg/m <sup>3</sup>	
Phosphoric Acid	7664-38-2	New Zealand WES	TWA(8 hours): 1 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m<sup>3</sup>: milligrams per cubic metre

CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use in a well-ventilated area.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

**Skin/hand protection**

See Section 7.1 for additional information on skin protection.

**Respiratory protection**

None required.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Gel
<b>Colour</b>	Blue
<b>Odour</b>	Slight Odour, Characteristic Odour
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	< 1
<b>Melting point/Freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	<i>No data available.</i>
<b>Flash point</b>	> 100 °C [Test Method:Closed Cup]
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	1.1 g/ml - 1.2 g/ml
<b>Relative density</b>	1.1 - 1.2 [Ref Std:WATER=1]
<b>Water solubility</b>	Complete
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity/Kinematic Viscosity</b>	<i>No data available.</i>
<b>Volatile organic compounds (VOC)</b>	<i>No data available.</i>
<b>Percent volatile</b>	<i>No data available.</i>
<b>VOC less H2O &amp; exempt solvents</b>	<i>No data available.</i>
<b>Molecular weight</b>	<i>No data available.</i>

#### Nanoparticles

This material contains nanoparticles.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

### 10.5 Incompatible materials

Strong bases.

### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to Section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

**Based on test data and/or information on the components, this material may produce the following health effects:**

#### Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

#### Skin contact

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

**3M™ Scotchbond™ Universal Etchant (41263)****Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Phosphoric Acid	Dermal	Rabbit	LD50 2,740 mg/kg
Phosphoric Acid	Ingestion	Rat	LD50 1,530 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg
Aluminium Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Phosphoric Acid	Rabbit	Corrosive
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Minimal irritation
Aluminium Oxide	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Phosphoric Acid	official classification	Corrosive
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Mild irritant
Aluminium Oxide	Rabbit	No significant irritation

**Sensitisation:****Skin Sensitisation**

Name	Species	Value
Phosphoric Acid	Human	Not classified
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human and animal	Not classified
Polyethylene Glycol	Guinea pig	Not classified

**Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

**3M™ Scotchbond™ Universal Etchant (41263)**

Name	Route	Value
Phosphoric Acid	In Vitro	Not mutagenic
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic
Aluminium Oxide	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic
Aluminium Oxide	Inhalation	Rat	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Phosphoric Acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Phosphoric Acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Phosphoric Acid	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Polyethylene Glycol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not classified for male reproduction	Rat	NOAEL 5699 +/-1341 mg/kg/day	5 days
Polyethylene Glycol	Not specified.	Not classified for reproduction and/or development		NOEL N/A	
Polyethylene Glycol	Ingestion	Not classified for development	Mouse	NOAEL 562 mg/animal/day	during gestation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Phosphoric Acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Polyethylene Glycol	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Polyethylene Glycol	Inhalation	respiratory system	Not classified	Rat	NOAEL 1.008 mg/l	2 weeks



**3M™ Scotchbond™ Universal Etchant (41263)**

Polyethylene Glycol	Ingestion	kidney and/or bladder   heart   endocrine system   hematopoietic system   liver   nervous system	Not classified	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Aluminium Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminium Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Ecotoxic to terrestrial vertebrates**

## 9.3C Terrestrial vertebrate toxicity

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Phosphoric Acid	7664-38-2	Green algae	Experimental	72 hours	EC50	>100 mg/l
Phosphoric Acid	7664-38-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Phosphoric Acid	7664-38-2	Green algae	Experimental	72 hours	NOEC	100 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	Water flea	Experimental	24 hours	EC50	>100 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	Zebra Fish	Experimental	96 hours	LC50	>100 mg/l
Synthetic Amorphous	112945-52-5	Green Algae	Experimental	72 hours	NOEC	60 mg/l

**3M™ Scotchbond™ Universal Etchant (41263)**

Silica, Fumed, Crystalline Free						
Polyethylene Glycol	25322-68-3	Activated sludge	Experimental		EC50	>1,000 mg/l
Polyethylene Glycol	25322-68-3	Atlantic Salmon	Experimental	96 hours	LC50	>1,000 mg/l
Aluminium Oxide	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide	1344-28-1	Green Algae	Experimental	72 hours	EC50	>100 mg/l
Aluminium Oxide	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminium Oxide	1344-28-1	Green Algae	Experimental	72 hours	NOEC	>100 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Phosphoric Acid	7664-38-2	Data not available - insufficient			N/A	
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	Data not available - insufficient			N/A	
Polyethylene Glycol	25322-68-3	Experimental Biodegradation	28 days	BOD	53 % BOD/ThBOD	OECD 301C - MITI test (I)
Aluminium Oxide	1344-28-1	Data not available - insufficient			N/A	

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Phosphoric Acid	7664-38-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyethylene Glycol	25322-68-3	Estimated Bioconcentration		Bioaccumulation factor	2.3	Estimated: Bioconcentration factor
Aluminium Oxide	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

## SECTION 14: Transport Information

### New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: UN1805

Proper Shipping Name: PHOSPHORIC ACID SOLUTION

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Dangerous Goods in Excepted Quantities, Class 8

Hazchem Code: 2R

IERG: 37

### International Air Transport Association (IATA) - Air Transport

UN No.: UN1805

Proper Shipping Name: PHOSPHORIC ACID SOLUTION

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: III

Special Instructions: Dangerous Goods in Excepted Quantities, Class 8

### International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN1805

Proper Shipping Name: PHOSPHORIC ACID SOLUTION

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: III

Marine Pollutant: Not applicable.

Special Instructions: FORBIDDEN BY THIS MODE OF TRANSPORT, 3M DIVISION POLICY

## SECTION 15: Regulatory information

HSNO Approval number	HSR002555
Group standard name	Dental Products (Corrosive) Group Standard 2017
HSNO Hazard classification	Refer to Section 2: Hazard identification

### NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

### Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
-------------------	--------------

**3M™ Scotchbond™ Universal Etchant (41263)**

Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 8.2B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for all other substances)
Secondary containment	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 8.2B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for all other substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for a HSNO 9.1A substance); or 250 L or 250 kg (for a HSNO 8.2B substance); or 1,000 L or 1,000 kg (for all other substances)

**SECTION 16: Other information****Revision information:**

Complete document review.

<b>Document group:</b>	29-8286-6	<b>Version number:</b>	4.00
<b>Issue Date:</b>	04/03/2021	<b>Supersedes date:</b>	09/11/2020

**Key to abbreviations and acronyms****GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>**