

Material Safety Data Sheet Cover-Sheet – This page provides additional New Zealand specific information for this product and must be read in conjunction with the Safety Data Sheet (SDS) attached

Product Name: Transbond™ XT Light Cure Adhesive Kit (712-030, 712-035)

Manufacturer: 3M

SDS Expiry: 10 August 2027

Supplier Details: Henry Schein New Zealand
243-249 Bush Road, Rosedale, Auckland, 0632
PO Box 101 140, North Shore, Auckland 0745
Ph. 0800 808 855
www.henryschein.co.nz

Emergency Contacts: Poisons/Hazardous Chemical Info Centre –
0800POISON/0800764766 (24 Hours)
Phone 111 for Fire, Ambulance or Police

HSNO Class/Category: 6

HSNO Group Standard: Dental Products Subsidiary Hazard Group Standard 2020
HSR002558

Statements/Pictograms: As per attached Safety Data Sheet (SDS)

Date Prepared: This coversheet was prepared – December 2024

This SDS coversheet has been produced by Henry Schein NZ and has been prepared in accordance with NZ EPA advice on making overseas SDS compliant to HSNO Act. The above information is based on the present state of our knowledge of the product at the time of publication. It is given in good faith, no warranty is implied with respect to the quality or the specifications of the product. Users must satisfy that the product is entirely suitable for their purpose. The SDS and this coversheet may be revised from time to time, please ensure you have a current copy.



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	18-6881-9	Version number:	5.00
Issue Date:	10/08/2022	Supersedes date:	02/08/2020

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

IDENTIFICATION:

1.1. Product identifier

3M™ Unitek™ Transbond™ XT Light Cure Adhesive Kit (712-030, 712-035)

Product Identification Numbers

70-2020-8942-4 70-2020-8947-3 XR-0038-0491-5

1.2. Recommended use and restrictions on use

Recommended use

Orthodontic use

1.3. Supplier's details

Address: 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone: 136 136
E Mail: productinfo.au@mmm.com
Website: www.3m.com.au

1.4. Emergency telephone number

Company Emergency Hotline: EMERGENCY: 1800 097 146 (Australia only)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

11-9309-3, 07-6174-2

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

TRANSPORT INFORMATION

This KIT and its components are NOT classified as Dangerous Goods.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as

required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	11-9309-3	Version number:	6.00
Issue Date:	10/08/2022	Supersedes date:	12/05/2020

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Unitek™ Transbond™ XT Primer (712-034)

1.2. Recommended use and restrictions on use

Recommended use

Orthodontic use

1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Warning

Symbols

Exclamation mark |

Pictograms**Hazard statements**

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.

Precautionary statements**Prevention:**

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P337 + P313 IF eye irritation persists: Get medical advice/attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Causes mild skin irritation.
 Harmful to aquatic life.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	45 - 55
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	45 - 55
Hydroquinone	123-31-9	< 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.
Carbon dioxide.

Condition

During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Hydroquinone	123-31-9	ACGIH	TWA:1 mg/m3	A3: Confirmed animal carcin., Dermal Sensitizer
Hydroquinone	123-31-9	Australia OELs	TWA(8 hours): 2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitizer

Sk: Absorption through the skin may be a significant source of exposure.

8.2. Exposure controls**8.2.1. Engineering controls**

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

See Section 7.1 for additional information on skin protection.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Transparent Yellow
Odour	Slight Acrylate
Odour threshold	No data available.
pH	Not applicable.
Melting point/Freezing point	Not applicable.
Boiling point/Initial boiling point/Boiling range	Not applicable.
Flash point	> 104.4 °C [Test Method: Closed Cup] [Details: Polymerizes]
Evaporation rate	No data available.
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	Not applicable.
Flammable Limits(UEL)	Not applicable.
Vapour pressure	<= 110,316.1 Pa [@ 55 °C] [Ref Std: AIR=1]
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.14 g/ml [Ref Std: WATER=1]
Relative density	1.14 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	175 mm ² /sec [@ 23 °C]
Volatile organic compounds (VOC)	No data available.
Percent volatile as Text	Nil
VOC less H ₂ O & exempt solvents	No data available.
Molecular weight	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Light.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be

present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Rat	LD50 10,837 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Rat	LD50 > 11,700 mg/kg
Hydroquinone	Dermal	Rat	LD50 > 4,800 mg/kg
Hydroquinone	Ingestion	Rat	LD50 302 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Triethylene Glycol Dimethacrylate (TEGDMA)	Guinea pig	Mild irritant
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Rabbit	No significant irritation
Hydroquinone	Human and animal	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Triethylene Glycol Dimethacrylate (TEGDMA)	Professional judgement	Moderate irritant
(1-methylethylidene)bis[4,1-phenyleneoxy(2-	In vitro data	No significant irritation

hydroxy-3,1-propanediyl)] bismethacrylate		
Hydroquinone	Human	Corrosive

Skin Sensitisation

Name	Species	Value
Triethylene Glycol Dimethacrylate (TEGDMA)	Human and animal	Sensitising
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Mouse	Not classified
Hydroquinone	Guinea pig	Sensitising

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Triethylene Glycol Dimethacrylate (TEGDMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In Vitro	Not mutagenic
Hydroquinone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydroquinone	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	Mouse	Not carcinogenic
Hydroquinone	Dermal	Mouse	Not carcinogenic
Hydroquinone	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene Glycol Dimethacrylate (TEGDMA)	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation
Hydroquinone	Ingestion	Not classified for female reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
Hydroquinone	Ingestion	Not classified for male reproduction	Rat	NOAEL 150 mg/kg/day	2 generation
Hydroquinone	Ingestion	Not classified for	Rat	NOAEL 100	during

		development		mg/kg/day	organogenesis
--	--	-------------	--	-----------	---------------

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydroquinone	Ingestion	nervous system	May cause damage to organs	Rat	NOAEL Not available	not applicable
Hydroquinone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Triethylene Glycol Dimethacrylate (TEGDMA)	Dermal	kidney and/or bladder blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks
(1-methylethylidene)bis[4,1-phenyleneoxy (2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Hydroquinone	Ingestion	blood	Not classified	Rat	NOAEL Not available	40 days
Hydroquinone	Ingestion	bone marrow liver	Not classified	Rat	NOAEL Not available	9 weeks
Hydroquinone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 50 mg/kg/day	15 months
Hydroquinone	Ocular	eyes	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in

Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Common Carp	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Green algae	Endpoint not reached	96 hours	EC50	>100 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Green algae	Experimental	96 hours	EC10	1.1 mg/l
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	Zebra Fish	Experimental	96 hours	LC50	16.4 mg/l
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	Green algae	Experimental	72 hours	NOEC	18.6 mg/l
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	Water flea	Experimental	21 days	NOEC	32 mg/l
Hydroquinone	123-31-9	Activated sludge	Experimental	2 hours	IC50	71 mg/l
Hydroquinone	123-31-9	Green algae	Experimental	72 hours	EC50	0.053 mg/l

Hydroquinone	123-31-9	Rainbow trout	Experimental	96 hours	LC50	0.044 mg/l
Hydroquinone	123-31-9	Water flea	Experimental	48 hours	EC50	0.061 mg/l
Hydroquinone	123-31-9	Fathead minnow	Experimental	32 days	NOEC	>=0.066 mg/l
Hydroquinone	123-31-9	Green algae	Experimental	72 hours	NOEC	0.0015 mg/l
Hydroquinone	123-31-9	Water flea	Experimental	21 days	NOEC	0.0029 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Biodegradation	28 days	BOD	21 %BOD/ThO D	similar to OECD 301F
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	29 days (t 1/2)	
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	Experimental Biodegradation	28 days	CO2 evolution	85 % weight	OECD 301B - Modified sturm or CO2
Hydroquinone	123-31-9	Experimental Biodegradation	14 days	BOD	70 %BOD/ThO D	OECD 301C - MITI test (I)

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Bioconcentration		Log Kow	4.63	
Triethylene Glycol Dimethacrylate (TEGDMA)	109-16-0	Experimental Bioconcentration		Log Kow	2.3	
Hydroquinone	123-31-9	Experimental Bioconcentration		Log Kow	0.59	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State

regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au



Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	07-6174-2	Version number:	6.00
Issue Date:	14/08/2022	Supersedes date:	02/08/2020

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Unitek™ Transbond™ XT Light Cure Adhesive (712-031, 712-036, 712-066)

1.2. Recommended use and restrictions on use

Recommended use

Orthodontic use

1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1B.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product label.

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

Prevention:

P272 Contaminated work clothing should not be allowed out of the workplace.
P280E Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

None known.

2.4. Other hazards which do not result in classification

Toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Silane Treated Quartz	100402-78-6	70 - 80
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	10 - 20
Bisphenol A Dimethacrylate	24448-20-2	5 - 10
Silane Treated Silica	68611-44-9	< 2
Triphenylantimony	603-36-1	< 1
Diphenyliodonium Hexafluorophosphate	58109-40-3	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

No need for first aid is anticipated.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Do not get in eyes. Use personal protective

equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use in a well-ventilated area.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. See Section 7.1 for additional information on skin protection.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Tooth
Odour	Slight Acrylic
Odour threshold	<i>No data available.</i>

pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	<i>No data available.</i>
Flash point	No flash point
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>Not applicable.</i>
Flammable Limits(UEL)	<i>Not applicable.</i>
Vapor Density and/or Relative Vapor Density	<i>Not applicable.</i>
Density	1.95 g/cm ³
Relative density	1.95 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>Not applicable.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H₂O & exempt solvents	<i>No data available.</i>
Molecular weight	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Light.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Substance

None known.

Condition

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

This product may have a characteristic odour; however, no adverse health effects are anticipated.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Silane Treated Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Silane Treated Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	Rat	LD50 > 11,700 mg/kg
Bisphenol A Dimethacrylate	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A Dimethacrylate	Ingestion	Rat	LD50 > 35,000 mg/kg
Silane Treated Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silane Treated Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silane Treated Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Diphenyliodonium Hexafluorophosphate	Ingestion	Rat	LD50 32 mg/kg
Triphenylantimony	Inhalation-Dust/Mist		LC50 estimated to be 1 - 5 mg/l
Triphenylantimony	Dermal	Rat	LD50 > 2,000 mg/kg
Triphenylantimony	Ingestion	Rat	LD50 82.5 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Silane Treated Quartz	Professional judgement	No significant irritation
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Rabbit	No significant irritation
Bisphenol A Dimethacrylate	Rabbit	No significant irritation
Silane Treated Silica	Rabbit	No significant irritation
Diphenyliodonium Hexafluorophosphate	Rabbit	No significant irritation
Triphenylantimony	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In vitro data	No significant irritation
Bisphenol A Dimethacrylate	Rabbit	No significant irritation
Silane Treated Silica	Rabbit	No significant irritation
Diphenyliodonium Hexafluorophosphate	Rabbit	Mild irritant
Triphenylantimony	Rabbit	Mild irritant

Skin Sensitisation

Name	Species	Value
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Mouse	Not classified
Bisphenol A Dimethacrylate	Human	Sensitising
Silane Treated Silica	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Silane Treated Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silane Treated Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	In Vitro	Not mutagenic
Bisphenol A Dimethacrylate	In Vitro	Not mutagenic
Silane Treated Silica	In Vitro	Not mutagenic
Diphenyliodonium Hexafluorophosphate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Silane Treated Quartz	Inhalation	Human and animal	Carcinogenic.
Silane Treated Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
(1-methylethylidene)bis[Ingestion	Not classified for development	Rat	NOAEL 1,000	during gestation

4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate				mg/kg/day	
Silane Treated Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silane Treated Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silane Treated Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Diphenyliodonium Hexafluorophosphate	Inhalation	respiratory irritation	Not classified	Not available	Irritation Equivocal	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Silane Treated Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	Ingestion	endocrine system hematopoietic system liver heart skin gastrointestinal tract bone, teeth, nails, and/or hair immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Silane Treated Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not determined.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Silane Treated Quartz	100402-78-6		Data not available or insufficient for classification			N/A
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Common Carp	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Green algae	Endpoint not reached	96 hours	EC50	>100 mg/l
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Green algae	Experimental	96 hours	EC10	1.1 mg/l
Bisphenol A Dimethacrylate	24448-20-2	Water flea	Analogous Compound	48 hours	No tox obs at lmt of water sol	>100 mg/l
Bisphenol A Dimethacrylate	24448-20-2	Zebra Fish	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
Bisphenol A Dimethacrylate	24448-20-2	Green algae	Endpoint not reached	72 hours	EL50	>100 mg/l
Bisphenol A Dimethacrylate	24448-20-2	Activated sludge	Analogous Compound	3 hours	EC50	>=1,000 mg/l
Silane Treated Silica	68611-44-9		Data not available or insufficient for classification			N/A

Diphenyliodonium Hexafluorophosphate	58109-40-3	Water flea	Experimental	48 hours	EC50	9.5 mg/l
Triphenylantimony	603-36-1		Data not available or insufficient for classification			N/A

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silane Treated Quartz	100402-78-6	Data not available-insufficient	N/A	N/A	N/A	N/A
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Biodegradation	28 days	BOD	21 %BOD/ThOD	similar to OECD 301F
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-propanediyl)] bismethacrylate	1565-94-2	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	29 days (t 1/2)	
Bisphenol A Dimethacrylate	24448-20-2	Analogous Compound Biodegradation	28 days	BOD	65.1 %BOD/ThOD	OECD 301F - Manometric respirometry
Silane Treated Silica	68611-44-9	Data not available-insufficient	N/A	N/A	N/A	N/A
Diphenyliodonium Hexafluorophosphate	58109-40-3	Data not available-insufficient	N/A	N/A	N/A	N/A
Triphenylantimony	603-36-1	Analogous Compound Biodegradation	28 days	BOD	<20 %BOD/ThOD	OECD 301F - Manometric respirometry

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Silane Treated Quartz	100402-78-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
(1-methylethylidene)bis[4,1-phenyleneoxy(2-hydroxy-3,1-	1565-94-2	Experimental Bioconcentration		Log Kow	4.63	

propanediyl)] bismethacrylate						
Bisphenol A Dimethacrylate	24448-20-2	Modeled Bioconcentrati on		Bioaccumulatio n factor	7.2	Catalogic™
Bisphenol A Dimethacrylate	24448-20-2	Modeled Bioconcentrati on		Log Kow	6.6	Episuite™
Silane Treated Silica	68611-44-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Diphenyliodon ium Hexafluoropho sphate	58109-40-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Triphenylantim ony	603-36-1	Estimated Bioconcentrati on		Log Kow	6.02	Episuite™

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

3M Australia SDSs are available at www.3m.com.au