

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: OSTRON 100 Liquid
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Auxillary for dental technology
- Details of the supplier of the safety data sheet Henry Schein Dental

243-249 Bush Road, Rosedale Auckland 0632, NEW ZEALAND

Free Phone: 0800 808 855

· Further information obtainable from: Regulatory affairs

· Emergency telephone number: 0800 764 766 (National Poisons Centre)

2 Hazards identification

· Classification of the substance or mixture

Flammable liquids Category 2 H225 Highly flammable liquid and vapour.

Skin irritation Category 2 H315 Causes skin irritation.

Skin sensitisation Category 1 H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Category 2

H373 May cause damage to organs through prolonged or repeated exposure.

- · Label elements
- · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Exemptions

The product, regulated as an invasive medical device by the Regulation (EC) 2017/745, is exempted from labelling requirements for substances and mixtures (according to the provision of the Art 1.5).

· Hazard pictograms







GHS02

GHS07

GHS0

- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

N,N-dimethyl-p-toluidine

· Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

(Contd. on page 2)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 1)

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Store locked up.

 $Dispose\ of\ contents/container\ in\ accordance\ with\ local/regional/national/international\ regulations.$

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · Description:

Only substances required to be mentioned according to Annex II of regulation 1907/2006 are listed. Information on the other substances that may be present can be obtained upon request.

| Dangerous components: | | |
|-----------------------|--|----------|
| CAS: 80-62-6 | Methyl methacrylate | 90-<100% |
| EINECS: 201-297-1 | Flammable liquids Category 2, H225; Skin irritation Category 2, H315; Skin sensitisation Category 1, H317; Specific target organ toxicity - single exposure Category 3, H335 | |
| CAS: 99-97-8 | N,N-dimethyl-p-toluidine | 1-<2.5% |
| EINECS: 202-805-4 | Acute oral toxicity Category 3, H301; Acute dermal toxicity Category 3, H311; Acute inhalation toxicity Category 3, H331; Specific target organ toxicity repeated exposure Category 2, H373; Flammable liquids Category 4, H227; Hazardous to the aquatic environment chronic Category 3, H412 | |

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. Do not use mouth to mouth or mouth to nose resuscitation.

Take affected persons into fresh air and keep quiet.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water.

If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 2)

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed Allergic reactions
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

No further relevant information available.

· Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Remove persons from danger area.

Keep away from ignition sources.

Avoid contact with the eyes and skin.

Wear protective clothing.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Do not allow to penetrate the ground/soil.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid contact with the eyes and skin.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 3)

Do not spray onto a naked flame or any incandescent material.

- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store only in unopened original receptacles.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store in a cool place.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see section 7.

| Ingredients with limit values that require monitoring at the workplace: | | | |
|---|--|--|--|
| 80-62-6 Methyl methacrylate | | | |
| WES (New Zealand) | Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm | | |
| | skin, dsen | | |
| IOELV (European Union) | Short-term value: 100 ppm Long-term value: 50 ppm | | |

· DNELs

80-62-6 Methyl methacrylate

| Dermal | DNEL dermal | 13.67 mg/kg bw/day (man) (worker, l. te., syst.) |
|------------|-----------------|--|
| Inhalative | DNEL inhalation | 208 mg/m3 (air) (worker, l. te., syst.) |

· PNECs

99-97-8 N,N-dimethyl-p-toluidine

PNEC Aqua | 152.59 µg/L (freshwater)

- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

- · Respiratory protection: Suitable respiratory protective device recommended.
- · Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

· Form: Liquid · Colour: Clear

· Odour: Characteristic
· Odour threshold: Not determined.
· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined.
 Initial boiling point and boiling range: 100 °C
 Flash point: 10 °C

Flammability (solid, gas): Highly flammable.
 Auto-ignition temperature: Undetermined.
 Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Explosion limits:

Lower:
Not determined.
Vapour pressure:
Not determined.
Vapour density
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

• water: Fully miscible. • Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined.Kinematic: Not determined.

· Solvent content:

 \cdot VOC (EC) 0.0 g/l

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 5)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

80-62-6 Methyl methacrylate Oral LD50 6,000 mg/kg (rabbit) Dermal LD50 >5,000 mg/kg (rab) Inhalative LC50/4 h 29.8 mg/l (rat (f+m))

99-97-8 N,N-dimethyl-p-toluidine

| Oral | LD50 | 1,650 mg/kg (rat (f+m)) |
|------------|----------|-------------------------|
| | LD50 | >2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 1.4 mg/l (rat (f+m)) |

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- Repeated dose toxicity May cause damage to organs through prolonged or repeated exposure.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

No further relevant information available.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

99-97-8 N,N-dimethyl-p-toluidine

LC50/96h | 46 mg/L (fish)

- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · *Mobility in soil* No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 6)

· Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

| UN-Number NZS, IMDG, IATA | UN1247 |
|---|---|
| UN proper shipping name NZS | 1247 METHYL METHACRYLATE MONOMI STABILIZED |
| IMDG, IATA | METHYL METHACRYLATE MONOMER, STABILIZED |
| Transport hazard class(es) | |
| NZS | |
| | |
| Class | 3 (F1) Flammable liquids. |
| Label | 3 |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| Packing group NZS, IMDG, IATA | II |
| Environmental hazards: | |
| Marine pollutant: | No |
| Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): | 33 |
| EMS Number: | F-E,S-D |
| Stowage Category | C |
| Stowage Code | SW1 Protected from sources of heat. SW2 Clear of living quarters. |

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON 100 Liquid

| | (Contd. of page |
|---|--|
| · Transport in bulk according to Annex II of and the IBC Code | f Marpol Not applicable. |
| · Transport/Additional information: | Temperature control is not required, in regards to Special Provision 386. Product uses chemical stabilization. |
| · <i>NZS</i> | |
| · Limited quantities (LQ) | IL |
| · Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| · Transport category | 2 |
| Tunnel restriction code | D/E |
| · <i>IMDG</i> | |
| · Limited quantities (LQ) | IL |
| · Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1247 METHYL METHACRYLATE MONOMEI STABILIZED, 3, II |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

80-62-6 Methyl methacrylate

HSR001195

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labelling:

Methyl methacrylate

N,N-dimethyl-p-toluidine

· Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray.

(Contd. on page 9)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 8)

Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

· Relevant phrases

H225 Highly flammable liquid and vapour.

H227 Combustible liquid.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

- · Department issuing SDS: Regulatory affairs
- · Contact: msds@gc.dental
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

 $Flammable\ liquids\ Category\ 2:\ Flammable\ liquids\ -\ Category\ 2$

Flammable liquids Category 4: Flammable liquids – Category 4

Acute oral toxicity Category 3: Acute toxicity - Category 3

Skin irritation Category 2: Skin corrosion/irritation – Category 2

Skin sensitisation Category 1: Skin sensitisation – Category 1

Specific target organ toxicity - single exposure Category 3: Specific target organ toxicity (single exposure) - Category 3

Specific target organ toxicity - repeated exposure Category 2: Specific target organ toxicity (repeated exposure) – Category 2

Hazardous to the aquatic environment chronic Category 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- · Sources
- ECHA (http://echa.europa.eu/)
- EnviChem (www.echemportal.org)
- * Data compared to the previous version altered.

This version replaces all previous versions.

Disclaimer:

The information contained herein is believed to be true and accurate. However, all statements, recommendations
(Contd. on page 10)

Printing date 19.06.2024 Version number 4 Revision: 19.06.2024

Trade name: OSTRON_100_Liquid

(Contd. of page 9)

or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

N7